

GENERAL SPECIFICATIONS *

| | | |
|--|---------------|-------------|
| • L.O.A | 10,77m | 35'4" |
| • Hull length | 9,96m | 32'8" |
| • L.W.L. | 9,50m | 31'2" |
| • Beam | 3,57m | 11'9" |
| • Deep draft (Cast iron) | 2,00m | 6'7" |
| • Deep ballast weight | 1 580kg | 3,482 lbs |
| • Shallow draft (Cast iron) | 1,50m | 4'11" |
| • Shallow ballast weight | 1 860kg | 4,099 lbs |
| • Performance draft (Hydraulic retractable keel) | 1,25 - 2,550m | 4'1" - 8'4" |
| • Ballast weight performance | 1 506kg | 3,319 lbs |
| • Air draft (all masts), with aerial | 15,57m | 51'1" |
| • Light displacement | 5 470kg | 12,046 lbs |
| • Fuel capacity (standard) | 130L | 34 US Gal |
| • Fresh water capacity: | | |
| - standard | 231L | 61 US Gal |
| - Option | 130L | 34 US Gal |
| • Engine power | | |
| - standard | 21 HP | 21 HP |
| - Option | 30 HP | 30 HP |

ARCHITECTS / DESIGNERS

- Naval Architect: Marc Lombard
- Outside & interior design: Nauta Design

EC CERTIFICATION *

- Category A - 6 people
- Category B - 8 people
- Category C - 10 people

STANDARD SAILS DIMENSIONS *

| | | |
|-------------------------------|---------------------|-----------|
| • Classic mainsail (standard) | 31,00m ² | 334 sq ft |
| • Furling mainsail (Option) | 26,00m ² | 280 sq ft |
| • Self-tacking jib (standard) | 18,30m ² | 197 sq ft |
| • Furling genoa (106 %) | 26,10m ² | 281 sq ft |
| • Code 0 | 40,00m ² | 430 sq ft |
| • Asymmetric spinnaker | 80,00m ² | 861 sq ft |
| • Classical mast: | | |
| - I | 12,82m | 42'1" |
| - J | 3,65m | 12' |
| - P | 12,66m | 41'6" |
| - E | 4,15m | 13'7" |
| • Roller furling mast: | | |
| - I | 12,79m | 42' |
| - J | 3,65m | 12' |
| - P | 12,56m | 41'2" |
| - E | 4,50m | 14'9" |

PERFORMANCE SAILS (Requires standard classical mast)

| | | |
|------------------------------|---------------------|-----------|
| • Square top mainsail | 34,70m ² | 373 sq ft |
| • Genoa (on Flatdeck furler) | 27m ² | 290 sq ft |

* Provisional specifications, boat in process of certification.



STANDARD EQUIPMENT

CONSTRUCTION

- Design in accordance with European Directive requirements and according to CE certification
- Monolithic hull design in polyester
- Monolithic structural inner moulding bonded to the hull
- Fibreglass and balsa wood sandwich contact deck, with diamond pattern non-slip coating
- Hull-deck join screwed, bonded and trimmed with 1 bulwark
- Cast iron keel fixed with bolts and stainless steel backing plates
- 2 Underhung rudders with stainless steel stock
- White coloured hull - Grey metal hull graphics

DECK EQUIPMENT

RIGGING

- Standard mast $\frac{9}{10}$ anodized aluminum deck stepped, 2 aft-swept spreaders - Without backstay
- Anodised aluminum boom
- Discontinuous stainless steel standing rigging
- Rigid boom vang with tackle
- Self-tacking jib rigging with on-deck furler
- Mainsail stay rope on the roof (with 2 chainplates)
- 1 Self-tacking jib track with traveller
- Complete running rigging: Mainsail halyard, Genoa halyard with cleat on mast, Boom topping lift with cleat on mast, Mainsheet, 1 Self-tacking jib sheet
- 8 Clutches
- 2 Flag halyards

WINCHES

- 1 Self-tailing winch (H35.2 STA) to port, on the roof
- 1 Aluminum "Speed Grip" winch handle
- 1 Winch handle box

SAILS

- Classic Dacron mainsail with Natural UV protection, cross cut, semi full batten
- Self-tacking jib Dacron with UV protection Natural, horizontal cut
- Lazy jacks

MOORING LINES - MOORING

- Self-draining chain locker - Clench bolt - Hatch cover
- Single stem roller
- 6 Aluminum mooring cleats - Stainless steel chafing plate

SAFETY ON DECK

- Stainless steel pulpit 2 sections
- 2 Stainless steel pushpits
- 1 Lifebuoy support bracket
- Double guard lines and stainless steel stanchions
- Welded ring on pushpit for flag
- Emergency ladder on pushpit

COCKPIT

- Self-draining cockpit
- 1 Cockpit locker under port side bench
- 2 Lockers in cockpit bottom
- Side helm's seats (aft helm seats in trim)
- 1 Liferaft locker to aft of cockpit (Usable dimensions: 800mm x 505mm x 370mm / 2'7" x 1'8" x 1'3")
- Natural solid wood slatted cockpit benches (1,56m x 0,50m / 5'1" x 1'8")
- Polyester drop-leaf cockpit table, Stainless steel handrail
- Tilling position: Stainless steel steering wheels - 800mm diameter / 2'7" - Leather covered - Steering gear at the helm station - Steering line transmission system - Stainless steel handrail - 1 Cup holder
- 1 Steering compass to starboard of the companionway
- 2 Deck access points to tiller system
- 1 Emergency tiller
- Engine throttle and control panel on starboard
- 2 Hinged PMMA companionway doors - Sliding hatch made of PMMA
- 1 Fixed, telescopic stainless steel swimming ladder

SWIM PLATFORM / AFT TRANSOM (in trim level)


- Fully opening transom, convertible to bathing platform (2,35m x 0,70m / 7'9" x 2'4")
- Manual opening using hoist, assisted by 2 pull cylinders
- Teak decking on swim deck
- 1 Fixed, telescopic stainless steel swimming ladder



INTERIOR

- Alpi walnut woodwork
- Rovere Alevé type laminated floorboards
- Beige padding upholstery: Saloon & Cabins
- Néo 05 fabric interior upholstery
- Mattresses in the cabins, HR35kg/m3 foam

Standard version: 2 cabins + 1 head



COMPANIONWAY

- Headroom: 1,89m / 6'2"
- GRP saloon companionway coated with non-slip surface on the steps
 - 2 Stainless steel handrails covered with anthracite leather

SALOON

- Headroom: 1,90 - 1,85m / 6'3" - 6'1"
- 2 Lengthways saloon bench sets, can be used as a single berth: an extension cushion for the port side bench seat is stowed against the bulkhead under the chart table
 - Chart table with 2 drop-leaves and 2 central top-access storage spaces. For the retractable keel version, the dimensions of the table are larger to accommodate the keel raising system
 - Storage under bench seats
 - 2 LED ceiling lights
 - 1 USB socket on the 12V electrical panel
 - 2 Panoramic roof windows
 - 2 Hull portholes with curtain
 - 1 Flush deck hatch with fan, T44, blind and mosquito net

STARBOARD GALLEY

- L-shaped galley - To starboard
Headroom: 1,85m / 6'1"
- Worktop in compact Clay with painted wooden fiddles
 - 1 1 rectangular stainless steel sink (320mm x 300mm / 1'1" x 1')
 - 1 Mixer tap with hot/cold water under pressure
 - 1 Gas cooker 2 burners - Stainless steel oven on gimbal - Stainless steel protection handrail
 - Cool box 100 L / 26 US Gal top opening (Positive cold)
 - Storage and lockers
 - 1 Dual compartment slide-out bin (2 x 15L / 2 x 4 US Gal)
 - 1 230 V socket (in trim level)
 - 1 Opening porthole on coaming in the side window with mosquito net

PORT SIDE CHART TABLE

- Headroom: 1,85m / 6'1"
- Chart table with folding tray against the starboard bulkhead with shelves fitted with fiddles in the upper part
 - 12 V electrical panel nearby
 - 1 Adjustable LED spotlight
 - 1 230 V socket (in trim level)
 - 1 Single USB socket
 - 1 Fixed coaming window with pleated blind

OWNER'S CABIN

- Headroom: 1,86m / 6'1"
- 1 Central double bed (2,02m x 1,60m - 0,55m / 6'8" x 5'3" - 1'10")
 - 2 Hanging closets with 1 open shelf on top, open lockers along the hull
 - 2 Adjustable LED spotlights in the headboard
 - 1 dual USB port outlet on each side of the bed (in trim level)
 - 1 230 V socket (in trim level) - to port
 - 1 Flush deck hatch with fan, T44, blind and mosquito net
 - 2 Hull portholes with curtain
 - Double door

STARBOARD AFT CABIN

- Headroom: 1,80m / 5'11"
- 1 Double bed (2,00m x 1,60m x 1,30m / 6'7" x 5'3" x 4'3")
 - 1 Hanging closet with 1 open shelf on the top
 - 1 Bed access sideboard
 - 2 Adjustable LED spotlights in the headboard
 - 1 dual USB port (in trim level)
 - 1 230 V socket (in trim level)
 - 1 Opening porthole below cockpit seat with curtain (Mosquito net in trim level)

AFT PORT SIDE HEAD

- Access through saloon
Headroom: 1,92m / 6'4"
- Shower with plexiglass door - Self-draining storage bin - 1 Mixer tap - White polyester shower base
 - 1 Manual toilet
 - 1 80 L / 21 US Gal rigid holding tank
 - 1 Polyester basin - 1 Hot/cold water mixer tap
 - 1 Cabinet
 - 1 Mirror
 - Toilet accessories
 - 1 Opening porthole in coaming
 - 2 LED ceiling lights
 - 1 230 V socket (in trim level, except for 3 cabins 1 head version)

3 cabins 1 head version (Option)



The head has a shower function mixer tap (no 230 V socket in trim level)

2 SYMMETRICAL AFT CABINS

- Headroom: 1,80m / 5'11"
- 1 Double bed (2,00m x 1,40m x 1,13m / 6'7" x 4'7" x 3'8")
 - 1 Hanging closet with 1 open shelf on the top
 - 1 Bed access sideboard
 - 2 Adjustable LED spotlights in the headboard
 - 1 dual USB port (in trim level)
 - 1 230 V socket (in trim level)
 - 1 Opening porthole below cockpit seat with curtain (Mosquito net in trim level)



ENGINE

- Engine Yanmar Diesel (Propeller shaft):
 - 21 CV/HP (standard)
 - 29 CV/HP (Option)
- Engine control - Control panel in cockpit (To starboard)
- Engine compartment: Soundproofing foam - Ventilation: 2 Air intakes and 1 powered air expulsion
- 1 Alternator (12V / 125 Ah)
- 1 Rotomoulded diesel tank 130 L / 34 US Gal (below aft starboard cabin berth) - Gauge on electrical panel - 1 Deck filler
- Filters: Seawater - Diesel - Water separator
- Stainless steel shaft line
- Fixed three blades propeller
- 1 Engine access through companionway (opening with 2 gas struts)
- 2 Access to side engine: Head & Aft cabin

ELECTRICITY

- 12V circuit
- 1 AGM service battery (75 Ah) - 1 AGM engine battery (50 Ah)
- 1 Power distributor
- 12 V electrical panel (Fuses - Voltmeter - 1 Fuel gauge)
- 1 Single USB socket at chart table
- LED lighting: Overhead lights, Adjustable spotlight in cabins & at chart table
- LED navigation lights: 1 Masthead light - 1 Engine navigation light - 1 Anchor light on masthead

PLUMBING

- 1 Rotomoulded freshwater tank 206 L / 54 US Gal, under berth in forward cabin
- Electrical gauge on 12 V panel
- 1 Deck filler
- Pressurised electric water pump - Expansion tank - Inline filter
- 25 L / 7 US Gal Electric water heater (engine use) below saloon starboard bench
- 1 80 L / 21 US Gal rigid holding tank
- 1 Electric bilge pump - 1 Manual bilge pump
- 1 Electric shower drain pump

GAS

- Gas cylinder locker - starboard aft cockpit
- Regulator and safety tap
- Gas leak detector

MISCELLANEOUS ITEMS

- Smoke detector



TRIM LEVEL & PACKS

TRIM LEVEL

| | CONFORT | FAMILY |
|--|--|---|
| <ul style="list-style-type: none"> • Teak slatted aft platform • Helm seats, slatted teak • 1 Halyard bag (to port) • Hot/cold water cockpit shower • Galley: Compact sink cover with cutting board • Hifi Fusion + Interior loudspeakers & Waterproof exterior speakers • Dual USB socket: in the saloon (x 1), in the forward cabin (x 2), in the aft cabins (x1) • Full 230 V system (6 Inside sockets, 1 Shore power socket) • 40 Amperes battery charger • 2 AGM service batteries - 100 Ah (in lieu of standard - 75 Ah) • Mosquito nets for opening portholes • Saloon: LED indirect lighting • Galley: Stainless steel 2 burner oven/grill cooker on gimbal (in lieu of standard) | <ul style="list-style-type: none"> ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ | <ul style="list-style-type: none"> ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ |
| <ul style="list-style-type: none"> • 1 000 W Electric windlass + Remote control • Aft transom protection • Bow stainless steel protection • "Luxe" polyester drop-leaf cockpit table • Outboard engine bracket • Additional fresh water tank (130L / 53 US Gal) • Galley: Sea water foot pump with cool box draining function • Saloon & Cabins: Ventilators | | <ul style="list-style-type: none"> ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ ▪ |

ELECTRONICS PACKS: B&G

| | COASTAL | OFFSHORE |
|---|--|--|
| <ul style="list-style-type: none"> • To starboard: 1 Triton² Graphic display • Sensor (Log, Speedometer, Temperature) • Wind Sensor (Windvane, Anemometer) • Windex Windvane | <ul style="list-style-type: none"> ▪ ▪ ▪ ▪ | <ul style="list-style-type: none"> ▪ ▪ ▪ ▪ |
| <ul style="list-style-type: none"> • Starboard helmstation: 1 Multifunction touchscreen Zeus 7" wide wireless (GPS, Chart plotter, Card reader - Navionics Silver cartography included) - <i>The Triton display moves to the port side</i> • NAC3 autopilot + control (to port) • V60 VHF radio fixed to the chart table + AIS receiver function | | <ul style="list-style-type: none"> ▪ ▪ ▪ |

RIGGING PACKS (Incompatible with First Line Pack)

| | DOWNWIND | UPWIND | DOWNWIND + UPWIND |
|---|---|--|--|
| <ul style="list-style-type: none"> • 1 Starboard manual (H35.2 STA) rigging winch + Cadet Grey halyard bag • Polyester bowsprit with integrated anchoring gear and bobstay (for Code 0 and asymmetric spinnaker) • Asymmetrical spinnaker rigging / Code 0 (sheets, Blocks, Halyards) • Additional jammers (on the roof for the halyard or on the coaming for the Genoa sheet, depending on the pack) • Rigging run back to cockpit (except boom topping lift) • 2 Manual (H40.2 STA) genoa sheet winches + Aluminum "Speed Grip" winch handle + Winch handle box • Genoa sheet 3D adjustment rings on the roof (replacing the self-tacking jib track and the traveller) • Genoa sheet on furler, high resistance Dacron (to replace the standard self-tacking jib) | <ul style="list-style-type: none"> ▪ ▪ ▪ 1 Triple jammer, on starboard roof ▪ ▪ | <ul style="list-style-type: none"> ▪ ▪ ▪ 2 Double jammers, in coaming (1 to port, 1 To starboard) ▪ ▪ ▪ | <ul style="list-style-type: none"> ▪ ▪ ▪ 2 Double jammers, in coaming + 1 Single clutch, on the coachroof ▪ ▪ ▪ |

IN-MAST FURLER PACK

- The standard Dacron self-tacking jib is retained.
- Anodised aluminium ⁹/₁₀th in-mast furler, 2 sets of spreader bars
 - Dacron cross-cut mainsail



PERFORMANCE PACK

FIRST LINE ALU PACK (incompatible with the rigging packs)

Requires standard classic mast and a trim level

Boast supplied without sail - Performance sails optional

- Polyester bowsprit with integrated anchoring gear and bobstay (for Code 0 and asymmetric spinnaker)
- Flatdeck genoa furler
- Additional jammers: 1 Double jammer on coaming to port and starboard for mainsail sheet, genoa sheet, adjustment of Genoa sheet traveller (control line) + 1 Triple jammer on the roof for spinnaker halyard/code 0
- Performance, Punch, Dyneema core running rigging (Halyards: Mainsail, Genoa, Code 0, Asymmetric spinnaker)
- Genoa sheet 3D adjustment rings on the roof
- Asymmetrical spinnaker rigging / Code 0 (sheets, Blocks, Halyards)
- German system (Two-way mainsheet at the helm station)
- 1 Starboard manual (H35.2 STA) rigging winch + Cadet Grey halyard bag
- 2 Manual (H40.2 STA) genoa sheet winches + Aluminum "Speed Grip" winch handle + Winch handle box
- Performance hull decoration (Red sticker)

OPTIONS

HULL - DECK - COCKPIT

- Pearl grey gel-coat
- Slatted teak cockpit floor
- Synthetic covering for bottom of cockpit (flexible, removable covering with press stud attachment, imitation teak slats)
- "Luxe" polyester/wood cockpit table, Stainless steel handrail, 1 Waterproof USB socket for charging smartphone or using LED lighting (lighting not supplied), Central storage (15L / 4 US Gal), Cup holders - requires Comfort trim level
- Cover for "Luxe" cockpit table (Cadet Grey)
- Steering wheels covers (Cadet Grey)
- "Luxe" coachroof sprayhood (Cadet Grey)
- "Luxe" bimini (Cadet Grey)
- Cockpit seats Dolce 51
- 12 V tunnel bow thruster (Side Power) + Dedicated batteries and charger (50 Ah - 12V)
- 2 Mooring cleats on transom
- 3 folding blades propeller
- Mooring kit:
 - Delta 16 kg/32 lbs anchor (galvanized steel)
 - Chain (Diameter: 10mm / $\frac{3}{8}$ " - Length: 28m / 92')
 - Line (Diameter: 18mm / $\frac{11}{16}$ " - Length: 40m / 131')
 - 6 Fenders - M (Diameter: 200mm / 8" - Length: 635mm / 2'1")
 - 4 Moorings lines (Diameter: 16mm / $\frac{5}{8}$ " - Length: 12m / 39'4")
- Electric windlass (1 000 W) - Remote control (not compatible with Family trim level)
- Windlass control in cockpit with chain counter
- Access openings to port and starboard
- Outboard engine bracket (not compatible with Family trim level)
- Shore fresh water supply
- Stand + support plates on the hull (option required for grounding the retractable keel version)
- Opening porthole on the cockpit coaming + Mosquito screens in the aft cabins

B&G ELECTRONIC

- WR10 Wireless autopilot remote control
- AIS 500

RIGGING - SAILS

- Performance sail pack (implies pack First Line Alu): High resistance Dacron square-topped mainsail, 4 battens, Natural UV protection, cross cut + Genoa sheet on Flatdeck furler, high resistance Dacron, Natural UV protection, cross cut
- Code 0 on furler for mast with in-mast furling or standard mast - Mylar Taffetas (implies pack Downwind or First Line pack)
- Natural colour Lazy bag
- Self-tacking jib rigging (track and traveller) - implies pack Upwind or Upwind & Downwind pack

WINCHES

- 1 Port electric primary winch (H35.2 STAEH), in lieu of standard

INTERIOR EQUIPMENT

LAYOUT VERSIONS

- 2 cabins 1 head version
- 3 cabins 1 head version

AMBIANCE

- Interior woodwork: Alpi white oak
- Brown oak laminated floors (only with Alpi white oak woodwork)
- Interior upholstery according to colour chart
- Macadamia padding upholstery: Saloon & Cabins
- Companionway steps made from mixed wood on floor

ON BOARD COMFORT EQUIPMENT

- Sea water foot pump, in galley (with cool box drainage function)
- Additional fresh water tank (130L / 34 US Gal) below aft port side cabin bed
- Grey water recovery tanks (130L / 34 US Gal) for sailing in inland waters - Not compatible with additional water tank
- 16 000 BTU air conditioning full boat (only for use via shore power supply) - Not compatible with 3 cabin version
- 8 000 BTU air conditioning saloon and front cabin (only for use via shore power supply)
- 8 000 BTU Autonomous air conditioning on Lithium battery in forward cabin and saloon, operating duration: 3 hours on battery, useful when at anchor. + recharging and use of motor or shore power - (12V - 230V) (Not compatible with heating, inverter, lithium battery options - required Comfort or Family trim level)
 - Included:
 - 1 Dedicated 12 V/230 V - 2 000 W inverter (this inverter does not allow the onboard comfort options)
 - 3 Lithium batteries (90 Ah)
 - 1 60 Ah service battery charger (replacing the 40 Ah charger for the trim level)
 - Navicolor 3.5" screen for displaying the battery charge level
- Forced air heating fuel
- 1 12V / 230V inverter - 2 000 W
- Quiet Flush seawater electric toilet
- Shore fresh water supply
- 1 90 Ah lithium battery replacing the 2 AGM100 Ah service batteries (requires trim level). The engine battery is still AGM + Navicolor 3.5" screen for displaying the battery charge level